


Fully **Automatic**



Horizontal Band Sawing Machine

- Rugged & Heavy Duty
- **Better Cutting Performance**
- Highly Productive
- Higher Cutting Rate





Horizontal Band Sawing Machine, Model- HBM 250

HIGHLIGHTS:

The machine with a capacity to cut upto 250 diameter is distinguished by its robust and compact construction and its capability to cut a wide range of materials with maximum productivity. It is designed for use of Bi-metal bandsaws.

- It is suitable for cutting bars in bundles, tubes and different profiles.
- Wide and stepless range of cutting speeds.
- Length of cut can be set on a digital display within 0.1mm and upto a maximum of 400mm in single stroke.
- Number of pieces to be cut can be programmed and machine will stop after programmed number of pieces are cut.
- For longer cutting lengths multi-indexing upto 9 x 400 i.e. 3600mm is feasible

STANDARD FEATURES:

- Infinitely variable speed drive for band.
- Precise hydraulic down feed system
- Shuttle type auto hydraulic feed
- Hydraulic dual vice clamping system
- Programming No. of pieces with auto-shut-off
- Spring loaded carbide blade guides
- Out of stock shut-off
- Power driven blade cleaning brush
- Ideal wheel motion detector with blade stalling and breakage shut-off
- Multiple indexing for longer length cutting
- Split front vice
- Rapid approach & auto work height control
- Coolant system
- Gear box with worm and worm wheel
- One Bi-metal band saw blade
- Operating tool kit and manual
- Machine Lamp

OPTIONAL EQUIPMENT:

- Nesting Fixture for bundle clamping for max. width 100-200 and height 50-150.
- Roller stock table for 1.5 meter long
- Chip Conveyor
- Variable Vice Pressure
- Hydraulic band tensioning

SPECIFICATIONS:

Cutting Capacity		Ø 250 mm □ 300 x 175 mm
Blade Size		3505 x 34 x 1.1 mm
Blade Speed		25-100 m/min (Stepless)
Blade Tension		Spring loaded (Manual)
	Single stroke Multiple stroke	400 mm 9 x 400 mm
Work table height		700 mm
Motors	Blade drive Hydraulic Coolant	2.2/3.0 KW/HP 0.75/1.0 KW/HP 0.1/0.125 KW/HP
Machine weight		1250 Kg
Floor area L x B x H		1975 x 1880 x 1740 mm

Due to continuous improvement of the product, SPM reserves all rights to change the above specifications without any prior notice.



Corporate Office:

Sector A, Plot No. 4,5,6,7, Parvati Co-op. Ind. Estate, YADRAV-416 145, Dist: Kolhapur, Maharashtra (INDIA)

T:+91 2322 252590 F: +91 2322 252592

E: marketing@spmtools.in spmtools.ichal@gmail.com

U: www.spmtools.co.in

FIE Group Company

M/s. Sree Engineers

#11, 3rd Main, 4th Cross, 4th Phase, 7th Block, Banashankari 3rd Stage, BANGALORE -560085. T:+91 80 26695857, F:+91 80 26797895 C:+91 9448385857, E:sreeeng@vsnl.net

M/s. RGK Engineering Enterprises (P) Ltd.

No. 218, Karthik Krupa, saraswati Nagar, Vijay Nagar, BANGALORE -560040. T:+91 80 23381641, 23303110

F:+91 80 23147882 C:+91 9845018313

E: narayanan_rgk@yahoo.co.in

M/s. Quality Sales & Service

68/3/1A, Bidhan Nagar Road, KOLKATTA -700 007 T:+91 33 23566199, Telefax:+91 33 23566202

C:+91 9433111218

E: quality_org@yahoo.co.in, quality_org@rediffmail.com

M/s. Precimech India (P) Ltd.

A-402, Priyadarshini Society, Plot No. 17, Patpar Ganj, DELHI-110 092 T:+91 11 65266171, 22611292 C:+91 9810195966, E:pmikuk@gmail.com

M/s. Amey Engineers & Traders

B-23/27, Jeevan Pushpa, Behind Ambika Darshan, Nana Shankar Seth Road. DOMBIVLI (W)-421 202, Dist.: Thane T:+91 251 2480490, F:+91 251 2490918 C:+91 9324803266 E: aet@vsnl.com, ameyengineers@hotmail.com

Pune Region Contact: +91 9881236403